

スノーボード 2025-2026モデル 形状スペック一覧

品番	品名	サイズ	全長	有効エッジ	接雪長	ノーズ	テール長	ノーズ幅	ウエスト幅	テール幅	サイドカーブ	スタンス幅	セットバック	FT値		SW値
														F	T	
TC25HF	THE C	162	1620	1490	(1490)	(90)	(40)	253	200	242	11000/12000	440~560	(30BACK)	184	116	133
		172	1720	1590	(1590)	(90)	(40)	243	200	232	16000/17000	440~560	(50BACK)	138	90	112
		182	1820	1700	(1700)	(80)	(40)	244	201	231	19000/20000	440~560	(60BACK)	201	104	140
TC25SF	THE C	162	1620	1490	(1490)	(90)	(40)	253	200	242	11000/12000	440~560	(30BACK)	108	95	108
		172	1720	1590	(1590)	(90)	(40)	243	200	232	16000/17000	440~560	(50BACK)	99	90	108
		182	1820	1700	(1700)	(80)	(40)	244	201	231	19000/20000	440~560	(60BACK)	124	95	113
RG25	REGNA	154	1535	1195	(1160)	(205)	(170)	286	246	286	8200/7750	500~620	10BACK	80	86	69
		158	1575	1225	(1190)	(210)	(175)	289	249	289	8600/8150	500~620	10BACK	82	88	74
SY25	SYMARC	151	1505	1300	(1200)	(160)	(145)	295	244	285	8800/8200/9000	460~580	(40BACK)	104	75	112
		156	1565	1360	(1260)	(160)	(145)	300	250	290	9900/9200/10200	480~600	(40BACK)	116	79	117
		160	1605	1400	(1300)	(160)	(145)	304	255	294	10800/10000/11300	500~620	(40BACK)	118	81	122
		164	1645	1440	(1340)	(160)	(145)	307	260	297	11800/11200/13000	500~620	(40BACK)	118	93	127
SY25M	SYMARC MG	151	1505	1300	(1200)	(160)	(145)	295	244	285	8800/8200/9000	460~580	(40BACK)	135	94	134
		156	1565	1360	(1260)	(160)	(145)	300	250	290	9900/9200/10200	480~600	(40BACK)	174	103	140
		160	1605	1400	(1300)	(160)	(145)	304	255	294	10800/10000/11300	500~620	(40BACK)	176	105	145
		164	1645	1440	(1340)	(160)	(145)	307	260	297	11800/11200/13000	500~620	(40BACK)	162	126	150
TH25	THRUST	157	1575	1295	(1250)	(170)	(155)	299	252	289	9900/9200/10200	500~620	(40BACK)	114	95	110
		161	1615	1335	(1290)	(170)	(155)	303	257	293	10800/10000/11300	500~620	(40BACK)	116	98	113
		165	1655	1375	(1330)	(170)	(155)	302	254	292	11050/10250/11550	500~620	(40BACK)	118	99	115
		169	1695	1415	(1370)	(170)	(155)	303	254	293	11300/10500/11800	500~620	(40BACK)	118	99	118
GL25	GLIDE	157	1575	1175	(1130)	(255)	(190)	300	248	279	7500	480~600	(20BACK)	87	90	102
		161	1615	1215	(1170)	(255)	(190)	303	252	283	7850	500~620	(20BACK)	90	94	105
GR25	GRACE	147	1475	1085	(1040)	(250)	(185)	289	239	269	6700	440~560	(20BACK)	78	84	91
		151	1515	1125	(1080)	(250)	(185)	295	244	274	7050	460~580	(20BACK)	82	88	96
RE25	REV	150	1505	1165	(1130)	(190)	(185)	282	241	282	8050/7600	480~600	10BACK	91.18	85	80
		153	1535	1195	(1160)	(190)	(185)	285	244	285	8450/8000	500~620	10BACK	94.94	89	83
		156	1565	1225	(1190)	(190)	(185)	288	247	288	8900/8450	500~620	10BACK	100.58	91	86
		159	1595	1245	(1210)	(195)	(190)	292	250	292	9000/8550	500~620	10BACK	104.34	94	89
LU25	LUVARTH	148	1480	1090	(1060)	(295)	(125)	297	251	273	8100	440~560	(30BACK)	81	88	100
		153	1530	1125	(1105)	(300)	(125)	305	258	281	8300	460~580	(30BACK)	87	95	103
		158	1580	1160	(1140)	(310)	(130)	312	264	288	8500	460~580	(30BACK)	90	97	106
SM25	SMOOTH	138	1385	1065	(1030)	(180)	(175)	270	231	270	6600/7050/6600	420~540	10BACK	77	70	68
		142	1425	1085	(1050)	(190)	(185)	273	234	273	6900/7300/6900	440~560	10BACK	81	74	71
		146	1465	1125	(1090)	(190)	(185)	278	238	278	7250/7650/7250	460~580	10BACK	85	78	75
		150	1505	1165	(1120)	(195)	(190)	283	243	283	7650/8050/7650	480~600	10BACK	89	84	79
		152	1525	1175	(1140)	(195)	(190)	285	245	285	7800/8200/7800	500~620	10BACK	91	85	81
		154	1545	1195	(1160)	(195)	(190)	287	246	287	8000/8400/8000	500~620	10BACK	93	87	85
		154W	1545	1195	(1160)	(195)	(190)	298	257	298	8000/8400/8000	500~620	10BACK	90	83	88
		158	1585	1225	(1190)	(200)	(195)	290	249	290	8450/8850/8450	500~620	10BACK	99	91	88
		158W	1585	1225	(1190)	(200)	(195)	301	260	301	8450/8850/8450	500~620	10BACK	94	83	91
162W	1625	1265	(1230)	(200)	(195)	304	263	304	8900/9300/8900	500~620	10BACK	94	85	94		
SH25	STYLAHOLIC	138	1380	1050	(1030)	(200)	(200)	275	238	275	7000	420~540	CENTERED	74	66	69
		143	1430	1100	(1030)	(200)	(200)	282	243	282	7350	440~560	CENTERED	77	69	72
		148	1480	1140	(1070)	(205)	(205)	288	248	288	7600	480~600	CENTERED	84	75	76
		151	1510	1160	(1090)	(210)	(210)	291	251	291	7850	500~620	CENTERED	87	78	80
		154	1540	1190	(1120)	(210)	(210)	295	254	295	8100	500~620	CENTERED	90	80	83
		157W	1570	1210	(1140)	(215)	(215)	306	265	306	8350	500~620	CENTERED	86	78	87
160W	1600	1240	(1170)	(215)	(215)	309	268	309	8600	500~620	CENTERED	89	78	90		
NX25	NEXTAGE	143	1435	1105	(1070)	(185)	(180)	272	233	272	7600/7200	440~560	10BACK	70	65	80
		147	1475	1145	(1110)	(185)	(180)	277	237	277	8000/7600	460~580	10BACK	73	67	84
		150	1505	1165	(1130)	(190)	(185)	282	241	282	8050/7600	480~600	10BACK	76	70	88
		153	1535	1195	(1160)	(190)	(185)	285	244	285	8450/8000	500~620	10BACK	79	72	92
XP25P	4XP POWTWIN	155W	1545	1160	(1090)	(227.5)	(227.5)	300	261	300	8000	500~620	CENTERED	87	86	100
		158W	1575	1190	(1120)	(227.5)	(227.5)	303	264	303	8300	500~620	CENTERED	91	90	101
XP25	4XP	138	1380	1050	(980)	(200)	(200)	275	238	275	7000	420~540	CENTERED	61	60	77
		143	1430	1100	(1030)	(200)	(200)	282	243	282	7350	440~560	CENTERED	65	64	82
		148	1480	1140	(1070)	(205)	(205)	288	248	288	7600	480~600	CENTERED	72	70	86
		151	1510	1160	(1090)	(210)	(210)	291	251	291	7850	500~620	CENTERED	74	73	90
		154	1540	1190	(1120)	(210)	(210)	295	254	295	8100	500~620	CENTERED	76	75	95
		157W	1570	1210	(1140)	(215)	(215)	306	265	306	8350	500~620	CENTERED	72	72	97
160W	1600	1240	(1170)	(215)	(215)	309	268	309	8600	500~620	CENTERED	73	72	100		
SL25	SLEEK	138	1385	1065	(1030)	(180)	(175)	270	231	270	6600/7050/6600	420~540	10BACK	72	70	67
		142	1425	1085	(1050)	(190)	(185)	273	234	273	6900/7300/6900	440~560	10BACK	75	74	70
		146	1465	1125	(1090)	(190)	(185)	278	238	278	7250/7650/7250	460~580	10BACK	79	77	73
SS25	SMOOTH SHORTIE	120	1205	905	(870)	(170)	(165)	243	212	243	6300/5900	340~460	10BACK	54	50	66
		126	1265	955	(920)	(175)	(170)	251	217	251	6500/6100	340~460	10BACK	60	53	69
AH25	ACHSE	132	1325	1015	(980)	(175)	(170)	259	222	259	6750/6350	380~500	10BACK	65	56	72
		138	1375	1030	(990)	(192.5)	(192.5)	278	232	278	4900	400~520	CENTERED	57	54	74
		141	1405	1050	(1010)	(197.5)	(197.5)	282	235	282	5000	420~540	CENTERED	60	57	77
		144	1435	1080	(1040)	(197.5)	(197.5)	286	238	286	5150	440~560	CENTERED	63	60	80
		147	1465	1100	(1060)	(202.5)	(202.5)	293	246	293	5300	460~580	CENTERED	67	64	86
		150	1495	1130	(1090)	(202.5)	(202.5)	296	248	296	5500	460~580	CENTERED	70	67	89
DE25	DECLIC	153	1525	1150	(1110)	(207.5)	(207.5)	299	250	299	5700	480~600	CENTERED	73	70	92
		156	1555	1180	(1140)	(207.5)	(207.5)	302	252	302	6000	480~600	CENTERED	76	73	95
		135	1345	1000	(960)	(192.5)	(192.5)	274	229	274	4800	380~500	CENTERED	51	49	68
		138	1375	1030	(990)	(192.5)	(192.5)	278	232	278	4900	400~520	CENTERED	54	52	72
GW25	GROWENT	141	1405	1050	(1010)	(197.5)	(197.5)	282	235	282	5000	420~540	CENTERED	57	55	76
		144	1435	1080	(1040)	(197.5)	(197.5)	286	238	286	5150	440~560	CENTERED	60	58	79
		147	1465	1100	(1060)	(202.5)	(202.5)	293	246	293	5300	460~580	CENTERED	64	61	85
		150	1495	1130	(1090)	(202.5)	(202.5)	296	248	296	5500	460~580	CENTERED	67	64	88
GW25	GROWENT	153	1525	1150	(1110)	(207.5)	(207.5)	299	250	299	5700	480~600	CENTERED	70	67	91
		156	1555	1180	(1140)	(207.5)	(207.5)	302	252	302	6000	480~600	CENTERED	73	70	94